



# **XYT STACKED SYSTEM**

**ASME-NNNN-03-0365-0355xx**

**CHARON2HD XYT (DXR+) with AccurET Modular**

Data sheet

Version 1.0

***ETEL***

AXIS DESIGNATION			
Number of controlled axes	3		
Axes name	X (bottom axis)	Y (top axis)	Theta
Thrust transmitter: DD (direct drive) or ID (indirect drive)	DD	DD	DD

TESTING CONDITIONS	UNIT			
Position controller	-	Modular 300 (7/15A)		Modular 300 (4/7.5A)
Motion controller	-	UltimET		
Rated payload	kg	-	-	2
Rated inertia	kg.m <sup>2</sup>	-	-	0.018
Rated input voltage	VDC	300		96
Tool point position	mm	246.5 above bottom surface		
Ambient temperature	°C	22 ± 1		
Isolation system	-	QuiET		

DIMENSIONAL DATA	UNIT			
Width	mm	730		
Length	mm	839		
Height	mm	226.5		
Total stroke	mm or °	365	355	Infinite
Moving mass (without payload)	kg	30.6	11.4	-
Total mass (without payload)	kg	55		
Rotor inertia (without payload)	kg.m <sup>2</sup>	-	-	0.004

FORCE / TORQUE CAPABILITIES (1)	UNIT			
Peak force / torque	N or Nm	953	658	7.87
Continuous force / torque	N or Nm	350	185	1.74
Standstill force / torque	N or Nm	264	140	1.32
Max. detent force / torque (average to peak)	N or Nm	26	16	0
Static friction (maximal value)	N or Nm	25	25	1
Dynamic friction (maximal value)	N/(m/s) or Nm/(rad/s)	25	25	0.03

LOAD CAPACITIES	UNIT			
Maximum payload	kg	30		

DYNAMIC PERFORMANCE	UNIT			
Duty cycle	%	25	60	10
Maximum speed	m/s or rad/s	2	2	30
Maximum acceleration	m/s <sup>2</sup> or rad/s <sup>2</sup>	20	20	180
Typical position stability at 2 kHz	nm or arcsec	±40	±40	±0.08

ACCURACY	UNIT			
Positioning accuracy (without mapping)	µm or arcsec	±20		±30
Positioning accuracy (with mapping)	µm or arcsec	±1		±3
Unidirectional repeatability	arcsec	-	-	±1
Bidirectional repeatability	µm or arcsec	±0.4		±2
Horizontal straightness / radial runout	µm	±3	±3.5	±3.5
Vertical straightness / total axial error	µm	±2.5	±5	±3
Orthogonality	arcsec	±15		-
Roll	arcsec	±5	±10	-
Pitch	arcsec	±5	±25	-
Yaw	arcsec	±10	±10	-

WORKING ENVIRONMENT	UNIT			
Clean room compatibility (2)	-	ISO 2		

ELECTRICAL SPECIFICATIONS (1)		UNIT	X (bottom axis)	Y (top axis)	Theta
Motor type	-		Ironcore	Ironcore	Toothless
Motor model	-		LMS15-050-3QC	LMG10-050-3QB	TTB0126-030-3NA-239
Number of phases	-		3	3	3
<b>Kt</b> Force constant	N/Arms or Nm/Arms		85.3	51.2	1.23
<b>Ku</b> Back EMF constant (3)	Vrms/(m/s) or Vrms/(rad/s)		50.9	31	0.712
<b>Km</b> Motor constant	Nm/√W		44.3	27.3	-
<b>R20</b> Electrical resistance at 20°C (3)	Ohm		2.47	2.35	10.5
<b>L1</b> Electrical inductance (3)	mH		23.8	13.7	2.65
<b>Ip</b> Peak current	Arms		15	15	6.9
<b>Ic</b> Continuous current	Arms		4.2	3.71	1.47
<b>Is</b> Standstill current	Arms		3.18	2.81	1.11
<b>ns</b> Standstill speed	m/s or rad/s		0.15	0.16	0.0016
<b>Um</b> Max. input voltage	VDC		300	300	100
<b>Pc</b> Max. cont. power dissipation	W		73.5	55.9	41.9
<b>2τp</b> Magnetic period	mm		32	32	-
<b>2p</b> Number of poles	-		-	-	28

ENCODER CHARACTERISTICS		UNIT			
Encoder and signal type	-		Optical - incremental	Optical - incremental	Optical - incremental
Output signal	-		1 Vpp	1 Vpp	1 Vpp
Signal period or line count	μm or period/turn		4	4	18'000
Reference mark	-		One	One	One
Power supply	V		5	5	5

VACUUM CHARACTERISTICS		UNIT			
<b>Vacuum supply for wafer chuck</b>					
Vacuum at interface output	bar			-0.6	
<b>Vacuum supply for axis cleanliness</b>					
Vacuum flow	l/min		10	6	5

TYPICAL MOVE AND SETTLE TIMES		UNIT			
Move 1: 10 μm within ±100 nm window	ms			40	-
Move 2: 25 mm within ±100 nm window	ms			130	-
Move 3: 80 mm within ±100 nm window	ms			180	-
Move 4: 1 deg within ±40 μdeg	ms		-	-	100
Move 5: 180 deg within ±40 μdeg	ms		-	-	500

GUIDING ELEMENTS					
Type	-		Ball bearing	Ball bearing	Crossed roller bearing

MATERIAL AND FINISH					
Baseplate	-		Anodized aluminum	Aluminium & silicon alloy	Aluminum alloy
Carriage	-		Aluminium & silicon alloy	Anodized aluminum	Stainless steel

OPTIONS / ACCESSORIES / FEATURES					
Temperature sensors	-		Yes	No	No

According to the Machinery Directive 2006/42/EC, the system presently described falls into the "partly completed machinery" category and fully complies with it as long as the system is operated according to the working conditions described in the corresponding manual. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the system is used in an improper way.

**Notes:** The specifications given may be mutually exclusive. Unless stated otherwise, all measurements are made within the testing conditions.

- (1) Tolerances on electrical parameters are available on request.
- (2) Under vertical laminar flow conditions at 0.5 m/s . Measured at tool point level. Contact ETEL for more details.
- (3) Terminal to terminal.